

**APPENDIX A**

1 (Currently Amended). An acoustic agglomerator for agglomerating constituents, comprising:

an acoustic generator configured to communicate with an area containing a fluid having constituents, wherein the acoustic generator is operable to generate a ~~frequency~~ an amplitude modulated acoustic field without reliance on the fluid, wherein the ~~frequency~~ amplitude modulated acoustic field is applied to the fluid to enhance agglomeration of the constituents in the fluid.

2 (Original). The acoustic agglomerator of claim 1, wherein the fluid is further defined as a liquid.

3 (Original). The acoustic agglomerator of claim 1, wherein the fluid is further defined as a gas.

4 (Original). The acoustic agglomerator of claim 1, wherein the fluid is further defined as a combustion exhaust gas.

5 (Previously Presented). The acoustic agglomerator of claim 1, further comprising:

a second acoustic generator operable to generate a second acoustic field without reliance on the fluid, wherein the second

acoustic field is applied to the fluid to enhance agglomeration of the constituents in the fluid.

6 (Original). The acoustic agglomerator of claim 5, wherein the second acoustic field is modulated.

7 (Original). The acoustic agglomerator of claim 5, wherein the second acoustic field is amplitude modulated.

8 (Original). The acoustic agglomerator of claim 5, wherein the second acoustic field is frequency modulated.

9 (Currently Amended). The acoustic agglomerator of claim 8, wherein the acoustic generator also frequency modulates the acoustic field relative to a first frequency and the second acoustic generator frequency modulates the second acoustic field relative to a second frequency.

10 (Currently Amended). The acoustic agglomerator of claim 9, wherein the ~~acoustic generator amplitude modulates the acoustic field, and the second acoustic generator amplitude modulates the~~ second acoustic field acoustic field is also frequency modulated.

11 (Original). The acoustic agglomerator of claim 5, wherein the second acoustic field is frequency and amplitude modulated.

12 (Previously Presented). The acoustic agglomerator of claim 1, further comprising:

a plurality of acoustic generators operable to generate a plurality of modulated acoustic fields without reliance on the fluid, wherein the plurality of modulated acoustic fields are applied to the fluid to enhance agglomeration of the constituents in the fluid.

13 (Previously Presented). The acoustic agglomerator of claim 1, wherein the area is an exhaust duct, further comprising:

a plurality of acoustic generators operable to generate a uniform modulated acoustic field without reliance on the fluid along the length of the exhaust duct, wherein the uniform modulated acoustic field is applied to the fluid to enhance agglomeration of the constituents in the fluid.

14 (Original). The acoustic agglomerator of claim 1, further comprising:

a particle collection device to receive the fluid from the area, the particle collection device operable to remove at least a portion of the constituents from the fluid.

15 (Original). The acoustic agglomerator of claim 14, wherein the particle collection device is a filter.

16 (Original). The acoustic agglomerator of claim 14, wherein the particle collection device is an electrostatic precipitator.

17 (Original). The acoustic agglomerator of claim 14, wherein the particle collection device is a baghouse.

18 (Original). The acoustic agglomerator of claim 14, wherein the particle collection device is a cyclone separator.

19 (Original). The acoustic agglomerator of claim 14, wherein the particle collection device is a gravitational settling chamber.

20 (Original). The acoustic agglomerator of Claim 14, further comprising:

a hopper operably positioned to accumulate at least a portion of the constituents removed from the fluid by the particle collection device.

21 (Currently Amended). An acoustic agglomerator for

agglomerating constituents, comprising:

an acoustic generator configured to communicate with an area containing a gas having constituents, wherein the acoustic generator is operable to generate an amplitude modulated acoustic field without reliance on the gas, wherein the amplitude modulated acoustic field is applied to the gas to enhance agglomeration of the constituents in the gas.

22 (Currently Amended). The acoustic agglomerator of claim 21, wherein the ~~acoustic generator can generate an amplitude modulated~~ acoustic field is also frequency modulated.

23 (Previously Presented). The acoustic agglomerator of claim 21, wherein the acoustic generator can generate a frequency modulated acoustic field.

24 (Previously Presented). The acoustic agglomerator of claim 22, further comprising:

a second acoustic generator operable to generate a second modulated acoustic field without reliance on the gas, wherein the second modulated acoustic field is applied to the gas to enhance agglomeration of the constituents in the gas.

25 (Previously Presented). The acoustic agglomerator of claim

22, further comprising:

a plurality of acoustic generators operable to generate a plurality of modulated acoustic fields without reliance on the gas, wherein the plurality of modulated acoustic fields are applied to the gas to enhance agglomeration of the constituents in the gas.

26 (Previously Presented). The acoustic agglomerator of claim

23, further comprising:

a second acoustic generator operable to generate a second modulated acoustic field without reliance on the gas, wherein the second modulated acoustic field is applied to the gas to enhance agglomeration of the constituents in the gas.

27 (Previously Presented). The acoustic agglomerator of claim

23, further comprising:

a plurality of acoustic generators operable to generate a plurality of modulated acoustic fields without reliance on the gas, wherein the plurality of modulated acoustic fields are applied to the gas to enhance agglomeration of the constituents in the gas.

28 (Previously Presented). The acoustic agglomerator of claim

21, further comprising:

a plurality of acoustic generators operable to generate a plurality of modulated acoustic fields without reliance on the gas, wherein the plurality of modulated acoustic fields are applied to the gas to enhance agglomeration of the constituents in the gas.

29 (Original). The acoustic agglomerator of claim 28, wherein at least a first acoustic generator of the plurality of acoustic generators can generate a frequency modulated acoustic field.

30 (Original). The acoustic agglomerator of claim 28, wherein at least a first acoustic generator of the plurality of acoustic generators can generate an amplitude modulated acoustic field.

31 (Original). The acoustic agglomerator of claim 28, wherein at least a first acoustic generator of the plurality of acoustic generators can generate a first acoustic field at a first frequency, and at least a second acoustic generator of the plurality of acoustic generators can generate a second acoustic field at a second frequency.

32 (Original). The acoustic agglomerator of claim 31, wherein the at least a first acoustic generator can modulate the first acoustic field relative to the first frequency, and the at least

a second acoustic generator can modulate the second acoustic field relative to the second frequency.

33 (Original). The acoustic agglomerator of claim 32, wherein the at least a first acoustic generator can amplitude modulate the first acoustic field.

34 (Original). The acoustic agglomerator of claim 33, wherein the at least a second acoustic generator can amplitude modulate the second acoustic field.

35 (Original). The acoustic agglomerator of claim 28, wherein at least a first acoustic generator of the plurality of acoustic generators can generate a first acoustic field at a first amplitude, and at least a second acoustic generator of the plurality of acoustic generators can generate a second acoustic field at a second amplitude.

36 (Previously Presented). The acoustic agglomerator of Claim 21, further comprising:

a particle collection device to receive the gas from the area, the particle collection device operable to remove at least a portion of the constituents from the gas.



37 (Original). The acoustic agglomerator of claim 36, wherein the particle collection device is a filter.

38 (Original). The acoustic agglomerator of claim 36, wherein the particle collection device is an electrostatic precipitator.

39 (Original). The acoustic agglomerator of claim 36, wherein the particle collection device is a baghouse.

40 (Original). The acoustic agglomerator of claim 36, wherein the particle collection device is a cyclone separator.

41 (Original). The acoustic agglomerator of claim 36, wherein the particle collection device is a gravitational settling chamber.

42 (Original). The acoustic agglomerator of Claim 36, further comprising:

a hopper operably positioned to accumulate at least a portion of the constituents removed from the gas by the particle collection device.

43 (Currently Amended). An acoustic agglomerator for agglomerating constituents, comprising:

an acoustic generator configured to communicate with a fluid having constituents, wherein the fluid is in an open area, wherein the acoustic generator is operable to generate an amplitude modulated acoustic field without reliance on the fluid, wherein the amplitude modulated acoustic field is applied to the fluid to enhance agglomeration of the constituents in the fluid in the open area.

44 (Original). The acoustic agglomerator of claim 43, wherein at least a portion of the constituents are a biohazardous material.

45 (Original). The acoustic agglomerator of claim 43, wherein at least a portion of the constituents are chemicals.

46 (Original). The acoustic agglomerator of claim 43, wherein the open area is within a building.

47 (Currently Amended). The acoustic agglomerator of claim 43, wherein the ~~acoustic generator can modulate the amplitude of the acoustic field~~ acoustic field is also frequency modulated.

48 (Original). The acoustic agglomerator of claim 43, wherein the acoustic generator can modulate the frequency of the acoustic field.

49 (Original). The acoustic agglomerator of claim 43, wherein the acoustic generator can modulate the frequency and amplitude of the acoustic field.

50 (Original). The acoustic agglomerator of claim 43, wherein the open area includes liquid.

51 (Original). The acoustic agglomerator of claim 43, wherein the open area includes gas.

52 (Currently Amended). An acoustic agglomerator for agglomerating constituents, comprising:

an acoustic generator configured to communicate with an exhaust of a vehicle having constituents, wherein the acoustic generator is operable to generate an amplitude modulated acoustic field without reliance on the exhaust, wherein the amplitude modulated acoustic field is applied to the exhaust to enhance agglomeration of the constituents in the exhaust.

53 (Currently Amended). The acoustic agglomerator of claim 52, wherein the ~~acoustic generator can modulate the amplitude of the acoustic field~~ acoustic field is also frequency modulated.

54 (Original). The acoustic agglomerator of claim 52, wherein the acoustic generator can modulate the frequency of the acoustic field.

55 (Currently Amended). The acoustic agglomerator of claim 52, wherein the acoustic generator can modulated the frequency and amplitude of the acoustic field.

56 (Original). The acoustic agglomerator of claim 52, wherein the exhaust includes combustion exhaust gas.

57 (Original). The acoustic agglomerator of claim 52, wherein the exhaust includes gas.

58 (Original). The acoustic agglomerator of claim 52, wherein the exhaust includes liquid.

59 (Currently Amended). An acoustic agglomerator for agglomerating constituents, comprising:

an acoustic generator configured to communicate with an area with a fluid flow having constituents, wherein the acoustic generator is operable to generate an amplitude modulated acoustic field without reliance on the fluid flow, wherein the amplitude modulated acoustic field is applied to the fluid flow

to enhance agglomeration of the constituents in the area, and the acoustic generator applies the amplitude modulated acoustic field to the area at an angle arbitrary to a direction of the fluid flow.

60 (Original). The acoustic agglomerator of claim 59, wherein the fluid flow includes liquid.

61 (Original). The acoustic agglomerator of claim 59, wherein the fluid flow includes gas.

62 (Original). The acoustic agglomerator of claim 59, wherein the fluid flow includes combustion gas particulate.

63 (Currently Amended). The acoustic agglomerator of claim 59, wherein the ~~acoustic generator can modulate the amplitude of the acoustic field~~ acoustic field is also frequency modulated.

64 (Original). The acoustic agglomerator of claim 59, wherein the acoustic generator can modulate the frequency of the acoustic field.

65 (Original). The acoustic agglomerator of claim 59, wherein the acoustic generator can modulate the frequency and amplitude

of the acoustic field.

66 (Currently Amended). An acoustic agglomerator for agglomerating constituents, comprising:

an acoustic generator configured to communicate with an area containing a fluid with constituents, wherein the acoustic generator is operable to generate an amplitude modulated acoustic field without reliance on the fluid, wherein the amplitude modulated acoustic field is applied to the fluid to enhance agglomeration of the constituents in the area; and

a system operable to determine information about the constituents in the area, wherein the acoustic generator can modify the amplitude modulated acoustic field in response to the information.

67 (Original). The acoustic agglomerator of claim 66, wherein the system includes an opacity detector.

68 (Original). The acoustic agglomerator of claim 66, wherein the system includes a particulate analyzer.

69 (Original). The acoustic agglomerator of claim 68, wherein the system further includes an opacity detector.

70 (Original). The acoustic agglomerator of claim 66, wherein the modification to the acoustic field is a modification to the frequency of the acoustic field.

71 (Currently Amended). The acoustic agglomerator of claim 66, wherein the modification to the acoustic field is a ~~modulation~~ modification to the amplitude of the acoustic field.

72 (Cancelled).

73 (Cancelled).

74 (Currently Amended). The acoustic agglomerator of claim ~~71~~66, wherein the ~~modulation is a combination of frequency and amplitude modulation~~ modification to the acoustic field is a modification to the frequency and amplitude of the acoustic field.

75 (Currently Amended). The acoustic agglomerator of claim 66, wherein the modification to the acoustic field is a modification of ~~the~~ a modulation of the acoustic field.

76 (Currently Amended). The acoustic agglomerator of claim ~~75~~66, wherein the acoustic field is also frequency modulated.

77 (Currently Amended). The acoustic agglomerator of claim 7566, wherein the acoustic ~~field is amplitude modulated~~ generator can modulate the frequency of the acoustic field.

78 (Cancelled).

79 (Currently Amended). The acoustic agglomerator of claim 7875, wherein the modification is a modification of ~~the~~ a frequency modulation of the acoustic field.

80 (Currently Amended). The acoustic agglomerator of claim 7875, wherein the modification is a modification of ~~the~~ an amplitude modulation of the acoustic field.

81 (Currently Amended). The acoustic agglomerator of claim 7875, wherein the modification is a modification of both amplitude and frequency modulation of the acoustic field.

82 (Cancelled).

83 (Previously Presented). A method of decreasing the frequency of cleaning a filtration device, the method comprising:



providing a filtration device operable to filter a fluid stream having constituents;

generating a modulated acoustic field without reliance on the fluid stream;

applying the modulated acoustic field to the fluid stream at a point upstream of the filtration device, wherein the modulated acoustic field enhances an agglomeration of the constituents.

84 (Original). The method of claim 83, wherein the acoustic field is frequency modulated.

85 (Original). The method of claim 83, wherein the acoustic field is amplitude modulated.

86 (Original). The method of claim 83, wherein the acoustic field is both frequency and amplitude modulated.

87 (Original). The method of claim 83, wherein the acoustic field is a sinusoidal sound field.

88 (Original). The method of claim 83, wherein the acoustic field is a periodic sound field.